

# MSDS

Material Safety Data Sheet

Revised: 6/2010n

**PRODUCT NAME: Epoxy.com Product #902 and Epoxy.com Product #903 "A" Component**

**ITEM NUMBER: 902A & 903A**

**DESCRIPTION: Two component 100% solid Polyurethane Joint Sealant**

HMIS CODES:	H:*	2	F:	1	R:	0	P:	G
-------------	-----	---	----	---	----	---	----	---

## SECTION I - IDENTIFICATION

MANUFACTURER'S NAME: **Epoxy Systems, Inc.**  
 20774 W. Pennsylvania Ave. **Telephone: 352-489-1666**  
 EMERGENCY PHONE NO: 1-800-633-8253

## SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS / CAS #	OSHA PEL	ACGIH TLV	OSHA STEL	LD50/LC50	WT %

\*\*All Chemicals comprising this product are listed on the Toxic Substance Control Act (TSCA) inventory.\*\*

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	No data
Vapor Density	No data
Specific Gravity (H2O=1)	1.25 – 1.28
Evaporation Rate	N/A (butyl Acetate = 1.0)
Solubility in water	Slight
Appearance and odor	Pigmented, self-leveling and non-sag consistency, 100% solid solvent free

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point	> 200°F
Flammable limits in air by volume	LEL: N/A : UEL: N/A
Extinguishing media	In case of fire, use foam, dry chemical, carbon dioxide, or extinguishers. Water spray may be ineffective on the fire but may be used to control fire and closed containers for cooling.
Special Firefighting Procedures	Wear self-contained breathing apparatus with full facepiece and protective clothing. Avoid inhalation of vapor during a fire.
Unusual Fire and Explosion Hazards	None known

## SECTION V - REACTIVITY DATA

Stability	Stable
Conditions to avoid	Avoid water contamination.
Incompatibility (Materials to avoid)	None known.
Hazardous Decomposition or Byproducts	Combustion products: Oxides of carbon, nitrogen and sulfur on burning.
Hazardous Polymerization	Will not polymerize.

## SECTION VI - HEALTH HAZARD DATA

**Health risks and symptoms of exposure**

Inhalation	May cause mild respiratory irritation if exposed to high temperatures.
Skin Contact	May cause mild irritation causing redness, itching of skin.
Eye Contact	May cause tearing, burning of eyes.
Skin Absorption	No data
Ingestion	May cause irritation to mouth and stomach.

**Health hazards (acute & chronic):**

CARCINOGENICITY: NTP? NO ; IARC MONOGRAPHS: NO ; OSHA REGULATED: NO

**Medical conditions generally aggravated by exposure:** None known

**Emergency & First Aid Procedures**

Eyes	Immediately flush with plenty of water for at least 15 minutes. Keep eyelids open. Consult a physician immediately.
Skin	Wash material off with plenty of soap and water. If redness, itching or burning develops, consult a physician.
Inhalation	Under normal use, there should not be any problem. However if inhaled, remove person to fresh air. Aid in breathing, if necessary. Get medical help.
Ingestion	If swallowed dilute with water and immediately induce vomiting. (Do not give anything by mouth or induce vomiting to an unconscious person). Get medical attention promptly.

**SECTION VII - SAFE HANDLING & USE INFORMATION**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Collect the product and place in a suitable waste container. Clean the area of spill with soap and water. Do not let the waste into the drainage system. The waste can be solidified with the B-component and then disposed as solid waste.

**WASTE DISPOSAL METHOD.** Dispose the waste in accordance to federal, local, and state regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Prevent skin and eye contact. Do not store at high temperature and humidity conditions.

**OTHER PRECAUTIONS:** Individuals with existing respiratory disease such as chronic bronchitis, emphysema or asthma like conditions should not be exposed to the product (during application). Do not drink, eat, or smoke while working with the product. Wash before such an activity. **KEEP AWAY FROM CHILDREN.**

**SECTION VIII - CONTROL MEASURES/PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** Not required under normal conditions. However if required, wear MSHA/NIOSH approved organic vapor or charcoal filtered cartridge respirator.

**VENTILATION:** local and or mechanical exhaust.

**PROTECTIVE GLOVES:** Nitrile, neoprene, and butyl rubber gloves.

**EYE PROTECTION:** Chemical tight goggles, full faceshield in addition if splashing is possible.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WORK/HYGIENIC PRACTICES:** Tyvek, neoprene, butyl, nitrile rubber based clothing. Eyewash station and safety showers in the work area. Emergency safety plans if regulations require. Proper training of the usage and application of the products.

**SECTION IX – REGULATORY INFORMATION**

**Transportation:** DOT: Non-Regulated

**Sara Title III (Section 313 Toxic Chemical Information):**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Concentration</u>
None known		

**California Proposition 65:**

As per requirements of the Safe Drinking Water & Toxic Enforcement Act of California, USA (1986), the public is warned that materials used in this product may create an exposure to chemicals known to the State of California to cause cancer, birth defects, or reproductive harm. This warning is required by Section 25249.6 of the California Health and Safety Code.

{The following detectable components of this product are substances, or belong to classes of substances, known to the state of California to cause cancer and /or reproductive toxicity.}

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Concentration</u>
None known		

**HMIS Ratings:** Health: 2  
 Flammability: 1  
 Reactivity: 0  
 Protection: G (gloves, goggles, coverall/apron, respirator)

**Disclaimer:** The data set forth in this MSDS are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Epoxy Systems, Inc. makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.

# MSDS

## Material Safety Data Sheet

Revised: 6/2010

**PRODUCT NAME: Epoxy.com Product #902 and Product #903 (B-COMPONENT)**

**ITEM NUMBER: 902B & 903B**

**DESCRIPTION: TWO COMPONENT 100% SOLID POLYURETHANE SEALANT**

HMIS CODES:	H:*	2	F:	2	R:	1	P:	G
-------------	-----	---	----	---	----	---	----	---

### SECTION I - IDENTIFICATION

MANUFACTURER'S NAME: Epoxy Systems, Inc.

20774 W. Pennsylvania Ave. Dunnellon, FL 34431

Telephone: 802-899-2844

EMERGENCY PHONE NO: 800-633-8253

### SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS / CAS #	OSHA PEL	ACGIH TLV	OSHA STEL	LD50/LC50	WT %
Diphenylmethane Diisocyanate (MDI) #26447-40-5	0.005ppm	0.02ppm	0.02ppm		
Butyl Benzyl Phthalate #85-68-7	No data	No data	No data		

\*\*All Chemicals comprising this product are listed on the Toxic Substance Control Act (TSCA) inventory.\*\*

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	>400F
Vapor Density (Air = 1)	8.5 (MDI)
Vapor Pressure (mm Hg)	<0.0001 @20C (MDI)
Specific Gravity (H2O=1)	1.05
Evaporation Rate	Not applicable
Solubility in water	Will react slowly with water.
Appearance and odor	Pale yellow liquid mixture. Mild aromatic odor.

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point	427°F (COC)
Flammable limits in air by volume	LEL: N.av. : UEL: N.av.
Extinguishing media	In case of fire, use dry chemical, foam, carbon dioxide, halogenated agents. The reaction between water and hot isocyanate may be vigorous. Water usage will help cool down the containers.
Special Firefighting Procedures	Do not inhale vapors. Wear self-contained breathing apparatus with full-face piece and protective clothing.
Unusual Fire and Explosion Hazards	Water contamination will produce carbon dioxide. Do not reseal contaminated containers as pressure buildup may rupture them.

### SECTION V - REACTIVITY DATA

Stability	Stable under normal conditions.
Conditions to avoid	Avoid water contact, alcohol, amines, acids and alkalis.
Incompatibility (Materials to avoid)	This material will react with any materials containing active hydrogen group such as water, alcohol's, ammonia, amines, alkalis and acids.
Hazardous Decomposition or Byproducts	Combustion products: carbon dioxide, carbon monoxide, and nitrogen oxides trace amounts of hydrogen cyanide.
Hazardous Polymerization	May occur. High temperatures in the presence of alkalis, amines, and metal compounds will accelerator polymerization. Possible evolution of carbon dioxide gas may rupture closed containers.

## **SECTION VI - HEALTH HAZARD DATA**

### **Health risks and symptoms of exposure**

Inhalation	Inhalation may cause coughing, nausea, tightness of chest with difficulty in breathing, and headache.
Skin Contact	Skin contact may result to irritation causing redness and itching.
Eye Contact	In case of eye contact, possible eye irritation if not washed immediately. May result in tearing, redness and/or burning effect of eyes.
Ingestion	May cause irritation to mouth, pharynx, and esophagus and stomach tissues.

### **Health hazards (acute & chronic):**

CARCINOGENICITY: NTP? NO ; IARC MONOGRAPHS: NO ; OSHA REGULATED: NO

**Medical conditions generally aggravated by exposure:** Prolonged and repeated exposure may result to respiratory sensitization, asthma like conditions, central nervous depression (dizziness, nausea, headache etc), skin sensitization and allergic skin reactions (rashes, hive-like, acme's, itching, etc.)

### **Emergency & First Aid Procedures**

Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Keep eyelids wide open. Consult physician immediately to have eyes examined and treated accordingly.
Skin	Wash material off the skin with plenty of soap and water. If redness, itching, or burning develops, consult a physician immediately.
Inhalation	Remove person to fresh air. If not breathing, give artificial respiration, preferable mouth to mouth. If breathing is labored, give oxygen. Get medical help immediately. DO NOT GIVE ANY FOOD OR FLUIDS TO AN UNCONSCIOUS PERSON.
Ingestion	Give 1 to 2 glasses of water to drink. If gastrointestinal symptoms develop, consult medical personnel immediately. NEVER GIVE ANYTHING BU MOUTH TO AN UNCONSCIOUS PERSON.

## **SECTION VII - SAFE HANDLING & USE INFORMATION**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear protective equipment and clothing during cleanup. Soak up material with absorbent and shovel into a chemical waste container. Cover the container but do not seal, and remove from work area. Use decontamination solution of 0.5% liquid detergent, 3 – 8 % concentrated ammonium hydroxide and remaining water. Clean the area off spill with the solution.

**WASTE DISPOSAL METHOD.** Neutralize the waste with the decontamination solution. Let it stand for 48 hours, allowing carbon dioxide to vent away. Dispose the waste in accordance to federal, local, and state regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Prevent skin and eye contact. Avoid breathing vapors and mist. A sensitized person should not be allowed to exposed to the product. Store in tightly sealed containers to protect from atmospheric moisture. Store in dry area.

**OTHER PRECAUTIONS:** Individuals with existing respiratory disease such as chronic bronchitis, emphysema or asthma like conditions should not be exposed to isocyanates or related products. Do not drink, eat, or smoke while working with the product. Wash before such an activity. KEEP AWAY FROM CHILDREN. Keep away from ignition sources such as fire, flame, sparks etc.

## **SECTION VIII - CONTROL MEASURES/PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** Not required under normal conditions after mixing with the A-component. However if required, wear MSHA/NIOSH approved organic vapor or charcoal filtered cartridge respirator to avoid any inhalation.

**VENTILATION:** local and or mechanical exhaust.

**PROTECTIVE GLOVES:** Nitrile, neoprene, and butyl rubber gloves.

**EYE PROTECTION:** Chemical tight goggles, full faceshield in addition if splashing is possible.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WORK/HYGIENIC PRACTICES:** Tyvek, neoprene, butyl, nitrile rubber based clothing have excellent resistance polyisocyanate based products. Provide eyewash station and safety showers in the work area. Provide emergency safety plans if regulations require. Give proper training of the usage and application of the products.

## **SECTION IX – REGULATORY INFORMATION**

**Transportation:** DOT: Non-Regulated

### **Sara Title III (Section 313 Toxic Chemical Information):**

**Chemical Name                      CAS Number      Concentration**

None known

### **California Proposition 65:**

As per requirements of the Safe Drinking Water & Toxic Enforcement Act of California, USA (1986), the public is warned that materials used in this product may create an exposure to chemicals known to the State of California to cause cancer, birth defects, or reproductive harm. This warning is required by Section 25249.6 of the California Health and Safety Code.

{The following detectable components of this product are substances, or belong to classes of substances, known to the state of California to cause cancer and /or reproductive toxicity. }

**Chemical Name**                      **CAS Number**    **Concentration**

None known

**HMIS Ratings:** Health: 2  
Flammability: 1  
Reactivity: 1  
Protection: G (gloves, goggles, coverall/apron, respirator)

**WHMIS Rating (Canada):** Class B, Division 3, Class D, Division 2, Subdivision B.

**Disclaimer:** The data set forth in this MSDS are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Epoxy Systems, Inc. makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.